

BANHAM

PROTECT YOUR PROPERTY

OPERATIONS MANUAL

BANHAM L2000 (MARK II)
SECURITY DOUBLE CYLINDER AUTOMATIC DEADLOCKING DEADLATCH

To open the door from the inside

Lift the handle at the rear of the case to withdraw the lockbolt and move the door in the opening direction. Continue to hold the handle in the lifted position whilst opening the door until the autobolt projects and the lockbolt is held in the withdrawn position. Closing the door will automatically release the lock bolt and secure the door in the closed condition.

To lock the handle when vacating or when inside the premises

1. Open the door.
2. Insert the key in the inside cylinder and rotate to the stop.
3. Return the key to the central position and remove.

The handle will now be locked against movement and closing the door will automatically release the lockbolt to secure the door whilst leaving the handle in this locked condition.

To lock the handle when inside the premises

With the door in the closed position, push the button on the face of the lock into the lock to its fullest extent. The handle will now be locked against movement until the button is pulled out.

To open the door from the outside

Insert the key in the outside cylinder and rotate to the stop. Move the door in the opening direction whilst holding the bolt in the withdrawn position with the key until the autobolt projects and the lockbolt is held in the withdrawn position. Closing the door will automatically release the lockbolt and secure the door in the locked condition. It should be noted that this lock has a safety feature whereby the action of re-entering the premises will automatically release the locked inside handle thereby returning the lock to normal operation.

To hold the bolt in the withdrawn position

1. Lift the handle to withdraw the bolt.
2. Push on the button whilst pushing the bolt into the case until the button enters a small amount into the lock.

The bolt will now be held in the withdraw position until the button is pulled out.

Indicator Mechanism

To provide awareness of the state of security this product is fitted with an indicator that provides a simple but effective indication of the state of locking.

For maximum security the indicator must be flush with the surface of the lock when the door is closed. This shows that the lockbolt has fully thrown and the deadlocking mechanism is fully in place. If this is not so, examine the staple box to ensure that it is clear of obstructions and if necessary reposition the staple to ensure freedom for the bolt to enter.