




### Key features

- 2 megapixel (1920 x 1080) high resolution
- Full HD1080p real-time video
- True day / night
- Super low-light
- 3D digital noise reduction
- IP66 rating
- IR range: up to 30m
- Motorized VF lens optional

### Dimensions



BAN-B-MVF	
<b>Camera</b>	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.05 lux@F1.2, AGC on 0.08 lux@F1.6, AGC on 0 lux with IR
Shutter time	1/25s ~ 1/100,000 s
Lens	2.7 ~ 9mm @F1.2, angle of view: 101° ~ 30.4° -Z: Motorized VF lens
Lens mount	Φ14
Auto iris	DC drive
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
<b>Compression standard</b>	
Video compression	H.264 / MPEG4 / MJPEG
Bit rate	32 Kbps ~ 16 Mbps
Dual stream	Yes
<b>Image</b>	
Max. image resolution	1920 x 1080
Frame rate	50 Hz: 25 fps (1920 x 1080) 60 Hz: 30 fps (1900 x 1080)
Image settings	Saturation, brightness, contrast adjustable through client software or web browser
<b>Network</b>	
Network storage	NAS (iSCSI optional)
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
Security	User authentication, watermark
<b>Interface</b>	
Communication interface	1 RJ45 10M / 100M ethernet interface
<b>General</b>	
Operating conditions	-25 °C ~ 60 °C (-13°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10%, PoE (802.3af)
Power consumption	max. 9.5W -Z: max. 12W
Weather-proof rating	IP66
IR range	Approx. 20 ~ 30m
Dimensions	98 × 88.58 × 328.79 mm (3.86" × 3.49" × 12.94")
Weight	1700g (3.75 lbs)

### Available models

DS-2CD8255F-EI, DS-2CD8255F-EIZ

"-Z": Motorized VF lens

\* Product picture and technical specs subject to change without previous notice.  
For further information, please contact our local sales representatives.